

G3

Smart PINPAD

- Multiple MIS cable port
- Wi-Fi, USB, RS232
- Contactless / NFC, small amount payment
- E-signature



Specification

Processor	32-Bit CPU
Memory	128MB FLASH, 64MB RAM
Display	2.8" (240 x 320) Colorful LCD resistant touchscreen with signature capture functionality (optional)
Keypad	10 Numeric keys, 9 Function keys
Card Readers	Magstripe : Triple track, high coercivity, bi-directional Smart Card : EMV & PBOC approved Contactless : NFC 13.56MHz, support ISO14443, Type A/B/C, Mifare Card (optional)
Audio	Buzzer
Card Slots	PSAM : 3 SIM : 1
Device Ports	1 micro-USB 1 Multi-functions I/O (2 RS232+1 USB-Host+1 USB Device)
Data Transmission Mode	RS232 port / USB / Wi-Fi (optional)
Power	Input : 100-240V, 50-60HZ Output : 5V/1A
OS	LINUX
Size	L × W × H = 145mm × 80mm × 31mm , 290g
Environment	Operating temperature : 0°C to 50°C Storage temperature : -20°C to 60°C Humidity : 5% to 95% (non-condense)



Shenzhen Xinguodu Technology Co.,Ltd

Address:17B Jinsong Mansion, Terra Industrial & Trade Park Chegongmiao,Futian District, Shenzhen.
Fax:+86-755-8631-9990 Tel:+86-755-8631-9929 <http://www.nexgo.cn> E-mail:sales@xinguodu.com